
CLIP ON SOFT CLOSING CORNERS HINGES



- Hydraulic buffer
- Opening angle: 105 °
- Diameter of hinge cup: 35mm
- Height of hinge cup 11.5mm
- Distance of door drilling: 3-7mm
- Distance of cup holes center: 48mm


- Door thickness: 14-21mm
- Finishing: Nickel plated
- Main material: Cold-rolled steel
- Material thickness: 0.8 1.2 1.2 mm
- Packing: 50 pairs





HK	4	5	6	7	
0	37 -1	36 0	35 1	34 2	
3	37 -4	36 -3	35 -2	34 -1	
5	37 -6	36 -5	35 -4	34 -3	
	Χ				D





HK	4	5	6	7	
0		36 0.1	35 1.1		
3	37 -3.9	36-2.9	35-1.9	34-0.9	
5	37 -5.9	36-4.9	35-3.9	34-2.9	
	Χ				D



Hydraulic buffer

Opening angle: 105 °

Diameter of hinge cup: 35mm

Height of hinge cup 11.5mm

Distance of door drilling: 3-7mm

• Distance of cup holes center: 48mm

Door thickness: 14-21mm


Finishing: Nickel plated

Main material: Cold-rolled steel

Material thickness: 0.8 - 1.2 - 1.2 mm

Packing: 50 pairs






H K	4	5	6	7	
0	37 3.6	36 4.6	³⁵ 5.6	34 6.6	
3	37 0.6	36 1.6	35 2.6	34 3.6	
5	37 -1.4	36-0.4	³⁵ 0.6	34 1.6	
	X				D




- Hydraulic buffer
- Opening angle: 105 °
- Diameter of hinge cup: 35mm
- Height of hinge cup 11.5mm
- Distance of door drilling: 3-7mm
- Distance of cup holes center: 48mm

- Door thickness: 14-21mm
- Finishing: Nickel plated
- Main material: Cold-rolled steel
- Material thickness: 0.8 1.2 1.2 mm
- Packing: 50 pairs








	H K	3	4	5	
	0	29 2	28 2	27 2	
	2	29 0	28 0	27 0	
	4	29 -2	28 -2	27 -2	
ı		Χ			D



- Hydraulic buffer
- Opening angle: 165 °
- Diameter of hinge cup: 35mm
- Height of hinge cup 11.5mm
- Distance of door drilling: 3-7mm
- Distance of cup holes center: 48mm


- Door thickness: 14-21mm
- Finishing: Nickel plated
- Main material: Cold-rolled steel
- Material thickness: zinc alloy 1.8 1.2 mm
- Packing: 50 pairs





DHK	3	4	5	6	7
0	16	17	18	19	20
3	13	14	15	16	17
5	11	12	13	14	15





DHK	3	4	5	6	7
0	7	8	9	10	11
3	4	5	6	7	8
5	2	3	4	5	6